

TC SMART



Overview

With its new TC5 SMART heat press, Secabo opens up new innovative paths leading to even better performance. This latest development of the successful automatic knee-lever press Secabo TC5 introduces a world novelty to the market, which opens up a variety of new options to users: The controller of the TC5 SMART now comes equipped with a Bluetooth interface that allows for controlling the press via the free app Secabo Smart Transfer, while also providing access to a comprehensive function database. This allows users to: Simply enter the type of fabric and the transfer material and immediately retrieve the matching combinations of temperature, time and pressure. Additional features, such as the calculation of heat-up times and warning functions, make the app a valuable assistant for all common heat transfer methods. The new heat press Secabo TC5 SMART offers a work surface of 38 x 38 cm, is easy to use and robust in ongoing operation. The modular design allows for quick and easy installation of removable plates in various formats, a quick change system and a slide extension.

Features



Bluetooth interface

The device can be connected and controlled via Bluetooth with a mobile device and the Secabo Smart Transfer App.




Secabo Smart Transfer App

The device is ready for control via the Secabo app. With the aid of this app, suitable transfer parameters can be selected for your application.



Digital controller

Duration and temperature can easily be adjusted and monitored using the digital controller.



Large workspace

Due to the large folding angle of 40°, the transfer objects can be aligned comfortably and precisely.



Low hysteresis

A state-of-the-art controller reduces the temperature fluctuations to a minimum, thus ensuring consistently good transfer results.



Variable work pressure

The work pressure is easy to adjust - in each case matching the transfer object and procedure.



Opens automatically

The heat press automatically opens after the set time has elapsed.



Safe working

The safety and quality of this device is constantly monitored - according to German safety standards.



Precise temperature distribution

The high-quality heat plate ensures an exact temperature distribution over the entire heating surface.



Replaceable plates

Interchangeable base plates available - also in combination with a quick-change system

Technical Data

Dimensions open	41cm x 93cm x 67cm
Dimensions closed	41cm x 57cm x 73cm
working area	38cm x 38cm
scope of delivery	Mechanical base, heating plate and base plate, controller box, C13 power supply cable, tools, operating instructions
pressure setting	the heating plate can be adjusted with a hand reel
max. downforce	250 g / cm ²
max temperature	225 °C
maximum time preset	999 s
max. clam angle	40 °
power supply	AC voltage 230V / 50Hz - 60Hz, 1.8kW
environment	+5°C - +35°C / 30% - 70% humidity
weight without packaging	32.00 kg
weight with package	39.00 kg
Brand	Secabo

Views

